




# MILLENNIUM METALS, INC.

10200 EASTPORT ROAD JACKSONVILLE, FL 32218  
LOCAL 904-358-8366 WATTS 1-877-358-Roof (7663)  
FAX 904-358-8285 MMI2000.NET

## 5-V CRIMP



## MILLENNIUM - V



Sidelap Detail

### PITCH ALERT:

THIS PRODUCT SHOULD NOT BE USED ON APPLICATIONS LESS THAN 3:12 PITCH WITHOUT A SECONDARY UNDERLAYMENT SUCH AS PEEL & SEAL AND SIDE LAP SEALANT APPLIED TO ANTI-SIPHON CHANNEL. THE MINIMUM PITCH ALLOWANCE WITH THE SECONDARY UNDERLAYMENT AND SIDE LAP SEALANT IS 2:12.

### Specifications:

Gauge	Finishes	Nominal Thickness	ASTM & Grade Specifications
29	Galvanized	.0142	ASTM A-653 Grade 80 Structural Steel
26	Galvanized	.0185	ASTM A-653 Grade 80 Structural Steel
26	Acrylic Galvalume	.0185	ASTM A-792 AZ55 Grade 80 Structural Steel
26	PTD Galvanized *	.0185	ASTM A-755 Grade 80 Structural Steel

PTD Material is siliconized polyester unless otherwise noted.

Millennium Metals Offers a Limited 40 year warranty on Painted Panels, 25 year limited warranty on Mill Finished Galvalume Panels.  
Please request warranty information from your distributor.


\* 26 Gauge Colors: Red, White, Gray, Hunter Green, Patina Green, Burnished Slate

### MILLENNIUM METALS INC.

TOLL FREE: 1-877-358-7663  
FAX: 904-358-8285  
MMI2000.NET

SUBJECT TO CHANGE WITHOUT NOTICE


PAGE 1



# MILLENNIUM METALS, INC.

10200 EASTPORT ROAD JACKSONVILLE, FL 32218  
LOCAL 904-358-8366 WATTS 1-877-358-Roof (7663)  
FAX 904-358-8285 MMI2000.NET

## 5-V CRIMP Installation Instructions:



## Roof Application:

*Step 1:* Make sure the deck is even and square. Millennium Metals recommends the use of a minimum  $\frac{1}{2}$ " plywood or OSB board attached in accordance with code. The deck must be supported by an engineered truss system not to exceed 24" on center. A moisture barrier such as 30# felt or other ASTM approved underlayment should be used over decking to control moisture. Metal should never come in direct contact with green or pressure treated lumber, as it will cause corrosion. If tin tabs are required to attach felt it will be necessary to apply a 15# felt in the direction of the panel as an additional separation barrier.

*Step 2:* Install Eave Drips/Roof Edge and Valleys according to details. Remember to use inside closure strips between Eave and Panel to eliminate water infiltration.

*Step 3:* Panel placement should begin on the gable end opposite the prevailing wind. Starter edge should be the lap edge. (Opposite of Purlin Bearing Leg) After laying first panel, check for squareness. Panel 2 should be lapped over purlin bearing leg of panel 1 with the lap edge. A minimum of 1" overhang is recommended at the eave. Alternative method of panel placement may begin in the center of the roof. Often this method is used when the area to be covered is not divisible by 2 ft. or traditional placement allows for a pipe flashing to occur in a side lap. Endlaps must be a minimum of 12" and two strips of butyl sealant tape is recommended 8" on the uphill side of the lap to keep watertight. The fastener should be placed between the butyl tape strips.

*Step 4:* Fasten panel according to detail B or C based on approved solid substrate selection. Detail C shows additional screws to be spaced on each side of major ribs for all eaves, ridges, and endlaps. Florida Product Approval requires the substrate to be plywood.


*Step 5:* Any field cutting must be done with metal nibblers, metal snips, or blades designed for metal cutting. No cutting should be done on the roof, as it will cause iron shavings to be spread and adhere to roof panels. Proper cutting should be done with the panels finished side down. Do not use graphite, lead, or any other marking devices that may stain panel and void warranty.

*Step 6:* Install the remaining accessories such as pipe boots; 5-V profile vents, ridge caps, gable flashings, butyl sealants, caulks, and closures are necessary to maintain watertight seals. Inspect screw fasteners to insure that they are installed properly.

## MILLENNIUM METALS INC.

TOLL FREE: 1-877-358-7663  
FAX: 904-358-8285  
MMI2000.NET




SUBJECT TO CHANGE WITHOUT NOTICE



# MILLENNIUM METALS, INC.

10200 EASTPORT ROAD JACKSONVILLE, FL 32218  
LOCAL 904-358-8366 WATTS 1-877-358-Roof (7663)  
FAX 904-358-8285 MMI2000.NET

Step 7: Fasteners should penetrate deck material by 1/4"

FASTENERS		
CORRECT	TOO LOOSE	TOO TIGHT
 EPDM MATERIAL VISIBLE AT WASHER. FASTENER IS PROPERTY INSTALLED.	 EPDM NOT AT VISIBLE JOINT. NOT ENOUGH COMPRESSION TO MAKE A SEAL.	 EPDM IS PANNED AND IS PROTRUDING BEYOND EDGE OF FASTENER.

#### Approximate Screw Chart

1 1/2" Plywood = 250 screws per square

1 3/4" Plywood = 150 screws per square

50 Lineal Feet = 1 Square

**Attention Installer:** Please refer to the important notes section of this manual for safety, storage, oil canning disclaimer, shaving disclaimer and underlayments prior to beginning this project.

#### **Important Notes:**

**Code Requirements** vary from project type and location. Millennium Metals recommends licensed roofing professionals to install materials. It is the responsibility of the roofing contractor to meet all prescriptive requirements if not indicated in our recommendations.

**Safety** when using metal materials is imperative. It is necessary to inspect deck integrity to insure it is safe to walk on before beginning any work. Never walk on material when wet or unsuitable weather conditions are present. Millennium Metals recommends the use of gloves and eye goggles when working handling materials. OSHA fall protection should be strictly adhered to on all projects.

**Job Specific engineering** should be considered for any Florida application not installed according to Florida product testing. Millennium Metals Inc has a third party engineer who can provide this documentation for a nominal fee. Millennium Metals Inc. accepts no responsibility for the information provided.

#### **Florida Product Testing**


Millennium Metals Inc. has Florida Product approval over 1/2" and 5/8" plywood. The current product approval is available on our website at mmi2000.net. Figure 2-1 and 2-2 indicate attachment for these approvals.

Fastener length for new construction should be a minimum of 1- 1/2" in the field of the project. The length of the fastener should penetrate the plywood a minimum of a 1/4".

#### **Re-Roofing Over Shingles**

If re-roofing over **one** layer of shingles with 1/2" or 5/8" plywood and felt a minimum of a 2-1/2" fastener should be used.

**A Limited Warranty** is available on Acrylic Galvalume and Pre-painted materials. A copy of this warranty is available to review at our website mmi2000.net. Failure to request warranty indicates customer accepts conditions stated within the warranty. Millennium Metals warrants material only. Long life fasteners are required in warranty content. Please consult us if you have any questions regarding fastener selection. Watertight warranties are not available.



# MILLENNIUM METALS, INC.

10200 EASTPORT ROAD JACKSONVILLE, FL 32218  
LOCAL 904-358-8366 WATTS 1-877-358-Roof (7663)  
FAX 904-358-8285 MMI2000.NET

**Estimating materials** is available through a third party. We accept no responsibility for the accuracy of this information. It is the sole responsibility of the customer/contractor to verify information. Changes to quantity, length, or accessories should be made prior to ordering.

**Metal Roofing Materials are special order products and therefore not returnable. Cancellations will not be honored if materials have been produced.**

**Materials should not be stored** in a place where moisture can penetrate the bundles or covered with plastic. If immediate installation is not possible, material should be placed on wood blocks to separate from the ground or concrete with one end elevated. The bands should be cut to allow material to expand. A loose canvas tarp should be used to cover material so that air can circulate. Improper storage will void warranty.


**Oil canning** is a wavy appearance in the surface of the panel. This condition is inherit to all metal panels but visible in designs with flat surfaces. This slight distortion in no way effects the warranty nor is reason for rejection or refusal.

**Shavings** are iron filings left from the cutting or drilling of steel materials. The iron particles tend to go airborne and settle on sheets. Failure to remove the particles will cause embedment of the iron and rust marks.

**Underlayments:** Consult your Millennium Metals Distributor about underlayments designed to be used with steel sheet roofing.




### Notes:




# MILLENNIUM METALS, INC.

10200 EASTPORT ROAD JACKSONVILLE, FL 32218  
904-358-8366 WATTS 1-877-358-7663 (ROOF)  
FAX 904-358-8285 MMI2000.NET

## DETAIL LOCATIONS







# MILLENNIUM METALS, INC.

10200 EASTPORT ROAD JACKSONVILLE, FL 32218  
LOCAL 904-358-8366 WATTS 1-877-358-Roof (7663)  
FAX 904-358-8285 MMI2000.NET


**A. STD EAVE DRIP (ED-1)**




**B. STD ROOF EDGE (EF-3)**




**C. STD GABLE TRIM (GR-4)**




**D. SIDEWALL FLASHING (SW-1)**




**E. PREFORMED VALLEY (PV-1)**




**F. PREFORMED VALLEY (PV-2)**




**G. ENDWALL FLASHING (EW-1)**




**H. VENTED RIDGE (RC-6)**



**I. STD HIP & RIDGE (RC-1)**



**J. TRANSITION FLASHING (TF-1)**



\*ALL HEMS ARE  $\frac{3}{8}$  OF AN INCH, UNLESS NOTED OTHERWISE.


## MILLENNIUM METALS INC.

TOLL FREE: 1-877-358-7663  
FAX: 904-358-8285  
MMI2000.NET

We stock screws, closures, touch up paint, pipe boots, butyl tape, ventilation and other accessories.

SUBJECT TO CHANGE WITHOUT NOTICE

PAGE 7




# MILLENNIUM METALS, INC.

10200 EASTPORT ROAD JACKSONVILLE, FL 32218  
LOCAL 904-358-8366 WATTS 1-877-358-Roof (7663)  
FAX 904-358-8285 MMI2000.NET


## RIDGE PITCH CHART

$\frac{2}{12}$	161°
$\frac{3}{12}$	152°
$\frac{4}{12}$	143°
$\frac{5}{12}$	134°
$\frac{6}{12}$	127°



## HIP / RIDGE DETAIL RC-1

\* 1 BOX VERSA VENT  
= 100 L.F. VENT  
= 50 L.F. RIDGE



## VENTED RIDGE DETAIL RC-6


### MILLENNIUM METALS INC.

TOLL FREE: 1-877-358-7663  
FAX: 904-358-8285  
MMI2000.NET

We stock screws, closures, touch up paint, pipe boots, butyl tape, ventilation and other accessories.


SUBJECT TO CHANGE WITHOUT NOTICE






# MILLENNIUM METALS, INC.

10200 EASTPORT ROAD JACKSONVILLE, FL 32218  
LOCAL 904-358-8366 WATTS 1-877-358-Roof (7663)  
FAX 904-358-8285 MMI2000.NET



EAVE DRIP DETAIL ED-1




ROOF EDGE DETAIL EF-3

## MILLENNIUM METALS INC.

TOLL FREE: 1-877-358-7663  
FAX: 904-358-8285  
MMI2000.NET


We stock screws, closures, touch up paint, pipe boots, butyl tape, ventilation and other accessories.

SUBJECT TO CHANGE WITHOUT NOTICE




# MILLENNIUM METALS, INC.

10200 EASTPORT ROAD JACKSONVILLE, FL 32218  
LOCAL 904-358-8366 WATTS 1-877-358-Roof (7663)  
FAX 904-358-8285 MMI2000.NET



GABLE DETAIL GR-4



NOTE: COUNTER-FLASHING  
OPTIONAL WHERE WALL  
COVERING CAN'T BE APPLIED  
OVER FLASHING WALL FLANGE.


SIDEWALL DETAIL SW-1

## MILLENNIUM METALS INC.

TOLL FREE: 1-877-358-7663  
FAX: 904-358-8285  
MMI2000.NET


We stock screws, closures, touch up paint, pipe boots, butyl tape, ventilation and other accessories.

SUBJECT TO CHANGE WITHOUT NOTICE




# MILLENNIUM METALS, INC.

10200 EASTPORT ROAD JACKSONVILLE, FL 32218  
LOCAL 904-358-8366 WATTS 1-877-358-Roof (7663)  
FAX 904-358-8285 MMI2000.NET



VALLEY DETAIL PV-1 & PV-2



PIPE BOOT  
CHART

#2	1 $\frac{3}{4}$ " - 3 $\frac{1}{4}$ "
#3	$\frac{1}{4}$ " - 4"
#4	3" - 6 $\frac{1}{4}$ "

\*Call Millennium Metals for high temp, retrofit and alternative boot sizes.


PENETRATION DETAIL

## MILLENNIUM METALS INC.

TOLL FREE: 1-877-358-7663  
FAX: 904-358-8285  
MMI2000.NET

We stock screws, closures, touch up paint, pipe boots, butyl tape, ventilation and other accessories.



SUBJECT TO CHANGE WITHOUT NOTICE



# MILLENNIUM METALS, INC.

10200 EASTPORT ROAD JACKSONVILLE, FL 32218  
LOCAL 904-358-8366 WATTS 1-877-358-Roof (7663)  
FAX 904-358-8285 MMI2000.NET

## TRANSITION DETAIL TF-1



**TRANSITION /  
ENDWALL PITCH  
CHART**

$\frac{2}{12}$	99°
$\frac{3}{12}$	104°
$\frac{4}{12}$	108°
$\frac{5}{12}$	113°
$\frac{6}{12}$	117°

NOTE: COUNTER-FLASHING  
OPTIONAL WHERE WALL  
COVERING CAN'T BE APPLIED  
OVER FLASHING WALL FLANGE.

## ENDWALL DETAIL EW-1

### MILLENNIUM METALS INC.

TOLL FREE: 1-877-358-7663  
FAX: 904-358-8285  
MMI2000.NET

We stock screws, closures, touch up paint, pipe boots, butyl tape, ventilation and other accessories.

SUBJECT TO CHANGE WITHOUT NOTICE